

**THE PRODUCTION OF BIODIESEL IN THE
PRESENCE OF CATALYST**

NUR'ATIQA BINTI MOHD SHAMSUDDIN

**Final Year Project Report Submitted in
Partial Fulfillment of the Requirement for the
Degree of Bachelor of Science (Hons.) Applied Chemistry
in the Faculty of Applied Sciences
Universiti Teknologi Mara**

MAY 2009


This Final Year Project Report entitled “**The Production of Biodiesel in the Presence of Catalyst**” was submitted by Nur’Atiqah binti Mohd Shamsuddin, in partial fulfillment of the Requirements for the Degree Bachelor of Science (Hons.) Applied Chemistry, in the Faculty of Applied Sciences and was approved by



Mdm. Haliza binti Kassim
Supervisor
B. Sc. (Hons.) Applied Chemistry
Faculty of Applied Science
Universiti Teknologi MARA
40450 Shah Alam
Selangor



Mr. Ahmad Faiza Mohd.
Co - Supervisor
B. Sc. (Hons.) Applied Chemistry
Faculty of Applied Science
Universiti Teknologi MARA
40450 Shah Alam
Selangor



Miss Sabrina M Yahaya
Project Coordinator
B. Sc. (Hons.) Applied Chemistry
Faculty of Applied Science
Universiti Teknologi MARA
40450 Shah Alam
Selangor



Assoc. Prof. Dr. Yusairie Mohd
Head of Programme
B. Sc. (Hons.) Applied Chemistry
Faculty of Applied Science
Universiti Teknologi MARA
40450 Shah Alam
Selangor

Date: 25 MAY 2009

ACKNOWLEDGEMENTS

Alhamdulillah, praise be to Allah S.W.T, the most merciful for granting me strengths, opportunity, and inspirations helpful throughout the completion of this project.

First, my thanks go to my supervisor, Mdm. Haliza binti Kassim for giving me her support and chance to work in the field of oleo chemical, which is different from her field of teaching. As an experience lecturer, she has shared all the knowledge and giving great support while doing this project. Her dedication and commitment to my works will always be appreciate and remembered.

Secondly, my special thanks go to Mr. Ahmad Faiza Mohd as my co-supervisor. I would like to thank to him due to his advice, assistance and support. His kindness, knowledge and continuous guidance in the oleo chemical field do help me lots in completing this project.

Lastly, for my beloved family and friends who always pray for my success and endless motivation and support during my study. My appreciation also goes to those who have been, directly or indirectly involved in the preparation and accomplishment of this study. Thank you for all the love, encouragement and cooperation given to me.

Nur'Atiqah binti Mohd.shamsuddin

TABLE OF CONTENTS

	Page
ACKNOWLEDGEMENTS	iii
TABLE OF CONTENTS	iv
LIST OF TABLES	vi
LIST OF FIGURES	vii
LIST OF ABBREVIATION	viii
ABSTRACT	x
ABSTRAK	xi
CHAPTER 1: INTRODUCTION	
1.1 Background	1
1.2 Problem statement	2
1.3 Significant of study	3
1.4 Objectives of study	3
CHAPTER 2: LITERATURE REVIEW	
2.1 Biodiesel features	4
2.1.1 Definition of biodiesel	4
2.1.2 Sources of biodiesel	6
2.1.3 Advantages of biodiesel	8
2.1.4 Disadvantages of biodiesel	9
2.1.5 Biodiesel economy in Malaysia	13
2.1.7 Social and environmental issues of biodiesel	16
2.2 Catalysts	18
2.2.1 Base catalyst - Potassium Hydroxide	18
2.2.2 Acid catalyst - ES-CAT 5500	19
CHAPTER 3: METHODOLOGY	
3.1 Material	21
3.1.1 Raw Material	21
3.1.2 Chemicals	21
3.1.3 Apparatus	21
3.1.4 Instrument	22

ABSTRACT

THE PRODUCTION OF BIODIESEL IN THE PRESENCE OF CATALYST

Biodiesel has been obtained by transesterification of palm oil with methanol in the presence of potassium hydroxide (KOH) as base catalyst and ES-CAT5500 as acid catalyst. Transesterification is a process of converting triacylglycerol to methyl ester. Parameter such as temperature, the type of reactant, amount and type catalyst used in this study is carefully manipulated since each parameters are dependent on each other and efficiency of transesterification process is based on these parameters. The yield of base biodiesel obtained in this study is 95.09% while the yield of acid biodiesel is 74.54%. Qualitative analysis of biodiesel is determined by using GCMS. Percent recovery of biodiesel is calculated by analyzing with GC-FID. The energy content in each biodiesel also is determined by using bomb calorimeter. Base biodiesel shows the amount of energy content of 39368J/g and 38888J/g is obtained from acid-biodiesel.